



LYNGDORF D-5 IC N

COMPACT IN-CEILING SPEAKER WITH CLOSED CABINET
AND ANGLED, ADJUSTABLE TWEETER

D STANDS FOR DISCREET

D stands for discreet – all models are designed as installation speakers for discreet in-wall or in-ceiling integration, featuring a wall-fixing mechanism with mounting legs. The models also come with their own loudspeaker enclosure, making system planning and the actual installation as easy as possible, with no after-market backbox or closed wall cavity required. This also ensures that the sound performance is always defined and consistent, depending less on the wall construction and the available space behind the wall.

D-5 IC N FOR IMMERSIVE AUDIO HEIGHT SPEAKERS

The D-5 IC N features an angled, adjustable tweeter. This construction allows the sound to beam from the ceiling towards the listening area when used as an in-ceiling height speakers for immersive audio. The N stands for a narrow enclosure, designed to fit narrow mounting spaces between joists and ceiling bars. The sound performance is similar to the D-5 model to achieve the best immersive sound experience.

SPECIFICATIONS

Model: Lyngdorf D-5 IC N

Description: 2 way speaker

Tweeter: 25 mm / 1" soft dome

Midrange driver: 180 mm, 35 mm voice coil, aluminum cone, vented magnet

Enclosure: Closed MDF cabinet

Frequency range: 80 – 20,000 Hz (-3 dB)

Nominal Impedance: 4 Ohm

Sensitivity: 88 dB (2.83V/1m)

Power handling: 100 W (IEC)

Maximum SPL: 105 dB

Crossover point: 2,2 kHz

Connections: Push-type spring terminal, gold-plated

Mounting: In-ceiling

Dimensions with grill (W x H x D): 358 x 358 x 113 mm / 14.1 x 14.1 x 4.45 inches

Cut-out dimensions (W x H x D): 286 x 334 x 109 mm / 11.3 x 13.2 x 4.3 inches

Weight: 6,2 kg / 13.7 lb

Finish: Matte black, white grill